


TECHNICAL SPECIFICATIONS


Specifications	Detail	5 Ton	8 Ton
Model No.		SM-FW 60CR-T1	SFA-96HC
Cooling capacity	BTU/Hr	60000	96000
Cooling capacity	KW	17.5	28.13
Heating Capacity	KW	N.A.	30.38
Rated input power	watts	6000	9004
Rated voltage/ph/frequency	Volts/Ph/Hz	380-3-50	380-3-50
Air Flow	m ³ / Hr	2200	4370
NOISE LEVEL			
Indoor Hi/Med/Lo	dB	53/50/47	60.9
Outdoor	dB	63	64.7
Compressor type		Scroll	Scroll
UNIT DIMENSION			
Indoor W x H x D	mm	600 x 1890 x 345	1200 x 1860 x 420
Outdoor W x H x D	mm	970 x 1245 x 400	1255 x 908 x 700
Weight Indoor / Outdoor	Kgs	65/114	158/174
PACKING DIMENSION			
Indoor W x H x D	mm	685 x 1985 x 450	1245 x 1980 x 455
Outdoor W x H x D	mm	1018 x 1380 x 435	1295 x 1025 x 700
PIPING CONNECTION			
Liquid Side	inch	1/2	1/2
Gas Side	inch	3/4	1 1/8



Trapeziform Innergroove Copper



Anti - Rust Cabinet



Hydrophilic Aluminum Fin

Trapeziform Innergroove Copper:

Compared with the triangular innergroove copper, the trapeziform innergroove copper allows more adequate refrigerant to flow through, improves heat exchange efficiency and reduces power consumption.

Hydrophilic Aluminum Fin:

In the indoor unit, the hydrophilic fins improve the cooling efficiency by enabling the condensated water flow freely between fins. In the outdoor unit, the hydrophilic fins improve the heating efficiency by accelerating the defrosting process.

The above specifications are subject to change without prior notice for product improvement



SAFARIO TRADING COMPANY L.L.C

P. O. Box 60091, Dubai, UAE.

H. O. Tel: 00971 4 2664081 / 2696964 , Fax: 00971 4 2621213

Email: safario@emirates.net.ae , www.safario.com